



1812-MTB-II Sealer-Tunnel

PRODUCT FEATURES

SEALERS

- 18" x 12" seal area
- Self-adjusting seal pads
- Easy quick change Mono seal wire
- Fully welded heavy duty seal head
- Fully welded 11 gauge steel frame
- Heavy duty automatic magnetic hold down
- Adjustable height seal area platform
- Auto seal temperature compensator
- Variable speed conveyor
- Stainless steel product loading tray
- Quick lock wire tensioners
- Pin wheel perforator

TUNNEL

- 12" wide 6" tall 20" long tunnel chamber
- Bottom heated solid conveyor belt
- High velocity blower
- Heat ducted to sides and top
- Thermostatic temperature control
- Variable speed 0-30 fpm conveyor
- Standard single plug for portability
- Finned Cal-rod heaters
- Durable electro-static powder finish
- 2000 watts of available heat
- Casters included

TWO YEAR WARRANTY (including seal wire)

Also available as an 1812-M-II without the sealer infeed conveyor

MODEL	MACHINE SIZE (LWH)	SHIPPING (SIZE/WEIGHT)	POWER REQUIRED	SEAL/TUNNEL AREA	PACKAGES PER MINUTE	MAX PRODUCT SIZE
1812-M-II L-SEALER	80" x 28" x 56"	87" x 30" x 59" 412 LBS.	115 VOLTS 20 AMPS	18" x 12" L x W	10-12	17" x 11" L x W
TUNNEL	ONE PIECE COMBO/UNIT	FULL SYSTEM INCL. ABOVE	SINGLE PLUG OPERATION	12" x 6" x 20" W x H x L	10-12	11" x 5" W x H