



## TD-20 Series Tunnels

### FEATURES

- Digital P.I.D. temperature control
- Automatic cool down circuit
- No maintenance mesh belt
- Adjustable air dampers
- High velocity blower
- Heat ducted to all 4 sides, top and bottom
- Variable speed 0-120 fpm conveyor
- Easy access slide out control panel
- Long life heavy duty Cal rod heaters
- Durable electro-static powder finish
- 12000 – 28000 watts of available heat\*\*\*
- Emergency stop buttons
- **TWO YEAR WARRANTY**

Model	Max Product Size	Packages Per Minute	Area	Power Required	Machine Size L x W x H	Shipping (Size/Weight) L x W x H
TD-20-12-1PH	19" x 11" W x H	60 - 75	20" x 12" x 52" W x H x L	220 Volts 1 PH 60 Amps	60" x 39" x 36"	92" x 42" x 54" 850 lbs.
TD-20-12-3PH	19" x 11" W x H	60 - 75	20" x 12" x 52" W x H x L	220 Volts 3 PH 40 Amps	60" x 39" x 36"	92" x 42" x 54" 850 lbs.
TD-20-19	19" x 18" W x H	60 - 75	20" x 19" x 52" W x H x L	220 Volts 3 PH 60 Amps	60" x 39" x 43"	92" x 42" x 61" 900 lbs.
TD-20-26	19" x 25" W x H	60 - 75	20" x 26" x 52" W x H x L	220 Volts 3 PH 70 Amps	60" x 39" x 50"	92" x 42" x 68" 950 lbs.

**Engineered to Perform. Designed to Endure.**

\*\*\*TD-20-12 single & 3 phase units -12000 watts of available heat

\*\*\*TD-20-19 – 20000 watts of available heat

\*\*\*TD-20-26 – 28000 watts of available heat



#### Charles Beseler Company

Packaging Division  
2018 West Main Street  
P.O. Box 431  
Stroudsburg, PA 18360

Toll Free: 800.237.3537  
P: 570.517.0400  
F: 800.966.4515  
Email: customerservice@beseler.com